



product



Specification

#017

Latex Seam Sealer



Capitol's 017 Latex Based, Carpet Seam Sealer is specially formulated to prevent edge raveling and seal seams of most residential carpet. 017 is compatible with most carpet backings. Do not use for sealing PVC backed products, or products where seam sealers are not required.

#017 is also a utility natural rubber fabric adhesive for binding, cloth tape seaming and face repairs. It has a quick drying, permanent bond that stays flexible

Description: Utility Natural Rubber Fabric Adhesive

Flammability: Non-Flammable

Open Time: 10 Minutes

Clean Up: Water when wet; Safety solvent or mineral spirits when dry.

Shelf Life: One year in closed container.

Limitations: Do not subject to temperatures below 40°F. Not freeze-thaw stable; protect from freezing. For interior use only.

Packaging:

- 1 Gallon (4/case)
- 1 Quart (12/case)
- 1/2 Pint (12/case)

For Use With: • Carpet Seams • Carpet Edging • Upholstery - Drapery • Fabric Laminating

Estimated Coverage:

- 640 lineal feet per quart
- 2,560 lineal feet per gallon

Directions: Apply with a paint brush, putty knife or "ketchup" bottle dispenser. For Seams: Apply an 1/8" bead with dispenser tip at carpet primary backing and immediately work latex between the primary and secondary backing. Allow to cure prior to seaming with hot melt carpet seam tape. When taping seams, coat both sides of tape fibers for good bond. **CLEAN UP:** Use a safety solvent or mineral spirits. **DO NOT USE ON PVC BACKED CARPETS OR VINYL SHEET GOODS.**

First Aid: Skin: Soap and water. Eyes: Flush with water, lifting upper and lower lids occasionally. Ingestion: Do not induce vomiting. Call physician or transport to an emergency facility. Inhalation: If affected, remove individual to fresh air. Use only in well ventilated areas.



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com

#017

Latex Seam Sealer

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: Capitol USA, LLC
Address: 300 Cross Plains Blvd.
Dalton, GA 30720
Telephone #: 1-800-831-8381
Emergency Phone: 800-535-5053
Generic ID: Natural Latex Seam Sealer
DOT Hazard Classification: None
Product Identity: #017 Latex Seam Sealer

SECTION II - HAZARDOUS COMPONENTS

Ammonia: % (By WT.) 0.66, PEL N.E.; TLV 50 ppm CAS #1336-21-6

SECTION III - PHYSICAL DATA

Initial Boiling Point: 212°F. Vapor Pressure: 760 mm Hg @ 100°F. Vapor Density (Air=1.0): 0.63. Specific Gravity: 0.94. G/L VOC (calculated): 0.00. Percent Volatiles: 32.0%.

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point: NA. Explosive Limit (Product): NA. Extinguishing Media: NA. Hazardous Decomposition Products: None. Special Fire Fighting Procedures: None. Unusual Fire & Explosion Hazards: None.

SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level: N.E. Threshold Limit Value: 50 ppm. Effects Of Exposure: Eyes - Possible mild irritation. Skin - None known. Breathing - None known. First Aid: Skin- Soap and water. Eyes - Flush with water, lifting upper and lower lids occasionally. Ingestion - Do not induce vomiting. Call physician or transport to an emergency facility. Inhalation - If affected, remove individual to fresh air. Use only in well ventilated areas.

SECTION VI - REACTIVITY DATA

Stability: Stable. Incompatibility: None. Hazardous Decomposition: None. Hazardous Polymerization: None. Conditions To Avoid: None Known.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material. Solidified materials accepted for landfill disposal in most locations. Check all local, state, and federal regulations.

SECTION VIII - PROTECTIVE EQUIPMENT

Ventilation: Open all available windows and entrances to insure good ventilation. Respirator Protection: None needed. Protective Gloves: None needed. Eye Protection: Wear glasses or protective goggles to avoid splashes. Other Protective Equipment: None required. Wash Hands Thoroughly with Soap and Water.

SECTION IX - SPECIAL PRECAUTIONS

Protect from freezing. Use only in applications as stated on the label. Do not take internally. Close container after each use. Avoid skin and eye contact.

Ventilation with fresh air, including open doors and windows should be observed during any flooring installation. Operate HVAC systems at 100% fresh air intake before, during and after installation to eliminate lingering odors or particulate matter. **KEEP OUT OF REACH OF CHILDREN**

Capitol USA believes the data set forth herein is accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com