

Specification

CB005

Acrylic Latex Cove Base Adhesive



CB 005 Acrylic Latex Cove Base Adhesive is the perfect compliment for Capitol USA's line of vinyl and rubber wall base. CB 005's acrylic formulation provides a strong, firm setting bond for years of trouble-free performance.

- Strong Early Grab for Corner Wrapping
- White Formulation Means Easier Cleanup
- Strong, Impact Resistant Bond
- Resists Shrinkage

Description: Acrylic Latex Based Cove Base Adhesive

Flammability: Non flammable

Open Time: 0 minute

Working Time: 45 minute

Shelf Life: One year in closed container.

Limitations: Do not subject to temperatures below 10°F. If frozen, warm to at least 70°F for 24 hours and stir before using. For interior use only.

Packaging: 4 Gallon • 1 Gallon (4/case) • 1 Quart (12/case) • 30-Ounce Cartridge (12 /case)

For The Installation Of:

- Vinyl Cove Base • Rubber Cove Base • Wall Carpet

For Use Over:

- Gypsum Drywall • Dry Concrete • Plaster
- Wood • Plywood • Brick • Scarified for wall carpet only (sanded) Plastic Laminates

Trowel Requirements

1/8 x 1/8 Sawtooth

Approx. 240 lineal feet of 4" Base per Gallon
65 - 70 square feet /gallon

- Vinyl Cove Base
- Rubber Cove Base
- Wall Carpet
- Cork Wall Tile

Instructions For Use:

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Make sure wall is free from grease, oil, paint, or old alcohol-resin adhesives that might interfere with the bond of the adhesive.
3. Spread adhesive with the correct trowel making sure to maintain trowel notchings throughout the installation.
4. Set cove base on to wall immediately. Press cove base to wall using a roller to insure proper adhesive transfer.
5. Clean wet adhesive and tools with white cloth and soap and water. Dried adhesives with mineral spirits.

Note: If applying adhesive with a cartridge gun, use a 2-hole nozzle for 2-1/2" base (~40 linear ft./tube), a 3-hole nozzle for 4" base (~25 linear ft./tube), and a 5-hole nozzle for 6" base (~15 linear ft./tube). Apply adhesive at least 1/4" from top of base if using a trowel and 1" from top of base if using a cartridge so that adhesive does not seep out as base is rolled. Bond base within 20 minutes of adhesive application.

CAUTION: Avoid contact with skin and eyes. If splashed in eyes, flush with copious amounts of water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed do not induce vomiting, call physician immediately. Keep container closed. **KEEP OUT OF REACH OF CHILDREN.**

