

Specification

TA380

Clear Thin Spread Vinyl Composition Tile Adhesive



- Sets up Quickly

Description: TA380 Clear Thin Spread Vinyl Composition Tile Adhesive

Flammability: Non-Flammable

Open Time: 45 minutes

Working Time: 24 hours

Clean Up: Clean wet adhesive and tools with white cloth and soap and water.

Shelf Life: One year in closed container.

Limitations: Do not subject to temperatures below 10°F. If frozen, warm to at least 70°F for 24 hours and stir before using.

Packaging:

- 4 Gallon • 1 Gallon • 1 Quart

For The Installation Of:

- Vinyl Composition Tile

For Use Over:

- Concrete • Plywood • APA Grade Particle Board • OSB • Terrazzo • Hardwood Floors • Latex-Portland Cement Underlayment • Gypsum or Cement Underlayment, existing VCT or Felt Backed Vinyl Sheet Goods must be primed with an acrylic sealer, such as Capitol's LL400 Liquid Latex) • Do not use over existing cutback

Trowel Requirements

1/16 x 1/16 x 1/16
18-19 square yards /gallon
160-170 square feet /gallon
• VCT (Vinyl Composition Tile)

Instructions For Use:

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the correct trowel making sure to maintain trowel notchings throughout the installation.
6. Allow the adhesive to flash for 45 minutes or until dry to touch prior to installing the flooring.
7. Apply only as much adhesive that can be installed within 24 hours.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturers recommendations.
10. Clean wet adhesive and tools with white cloth and soap and water.

Caution:

Avoid contact with skin and eyes. If splashed in eyes, flush with copious amounts of water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed do not induce vomiting, call physician immediately. Keep container closed. **KEEP OUT OF REACH OF CHILDREN**



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com

TA380

Clear Thin Spread Vinyl Composition Tile Adhesive

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: Capitol USA, LLC
Address: 300 Cross Plains Blvd.
Dalton, GA 30722
Telephone #: 1-800-831-8381
Emergency Phone: 800-535-5053
Generic ID: Latex Based Flooring Adhesive
DOT Hazard Classification: None
Product Identity: TA380 Clear Thin Spread
VCT Adhesive

SECTION II - HAZARDOUS COMPONENTS

None per OSHA Regulation: 29CFR1910.1200.
None per SARA Title III, Section 313 and
TSCA 40 CRF 372

SECTION III - PHYSICAL DATA

Initial Boiling Point: 212°F. Vapor Pressure:
Same as water. Vapor Density (Air=1.0): Same
as water. Specific Gravity: .99. G/L VOC (cal-
culated): 0.00. Percent Volatiles: 49%

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point: NA; Explosive Limit (Product):
NA; Extinguishing Media: NA; Hazardous
Decomposition Products: None; Special Fire
Fighting Procedures: None; Unusual Fire &
Explosion Hazards: None

SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level: NA; Threshold
Limit Value: NA; Effects Of Exposure: Eyes-
Possible mild irritation. Skin - None known.
Breathing - None known.

SECTION VI - REACTIVITY DATA

Stability: Stable; Incompatibility: None; Haz-
ardous Decomposition: None; Hazardous Pol-
ymerization: None; Conditions To Avoid:
None Known

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released

or Spilled: Absorb liquid on paper, vermicu-
lite, floor absorbent, or other absorbent mate-
rial. Solidified materials accepted for landfill
disposal in most locations. Check all local,
state, and federal regulations.

SECTION VIII - PROTECTIVE EQUIPMENT

Ventilation: Open all available windows and
entrances to insure good ventilation. Respira-
tor Protection: None needed. Protective
Gloves: None needed. Eye Protection: Wear
glasses or protective goggles to avoid
splashes. Other Protective Equipment: None
required. Wash Hands Thoroughly with Soap
and Water.

SECTION IX - SPECIAL PRECAUTIONS

Protect from freezing. Use only in applica-
tions as stated on the label. Do not take inter-
nally. Close container after each use. Avoid
skin and eye contact.

Ventilation with fresh air, including open
doors and windows should be observed dur-
ing any flooring installation. Operate HVAC
systems at 100% fresh air intake before, dur-
ing and after installation to eliminate linger-
ing odors or particulate matter.

KEEP OUT OF REACH OF CHILDREN

Capitol USA believes the data set forth herein
is accurate as of the date hereof, and makes no
warranty with respect thereto and expressly
disclaims all liability for reliance thereon.
Such data are offered solely for your consider-
ation, investigation and verification.



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com