



product Specification

Fast 095

Premium Performance Carpet Adhesive



FAST 095 is our Premium Performance Carpet Adhesive. FAST 095 is ideal for the installation of high-end patterned carpets or for installations that are exposed to a high amount of traffic.

- Very Fast Tack for Difficult to Install Carpet
- Superior Bond Strengths for High Traffic Areas
- Ideal for Double Glue Installations

Description: Fast 095 Premium Performance Carpet Adhesive

Flammability: Non-Flammable

Open Time: 0-15 minutes (For non-porous backings, allow full 15 minute open time.)

Working Time: 45 minutes

Clean Up: Clean wet adhesive and tools with white cloth and soap and water. Mineral spirits when dry.

Shelf Life: One year in closed container.

Limitations: Do not subject to temperatures below 10°F. If frozen, warm to at least 70°F and stir before using. For interior use only.

Packaging: 4 Gallon

For The Installation Of:

- Jute Backed Carpet • Urethane • ActionBac® Carpet
- Latex Unitary Carpet • Woven • Hot Melt Backed Carpet • Double Glue Installations

For Use Over:

- Concrete • Plywood • APA Grade Particle Board • OSB • Terrazzo • Hardwood Floors • Latex-Portland Cement Underlayment • Gypsum Cement Underlay





ment • VCT • Felt Backed Vinyl Sheet Goods (prime with an acrylic sealer, such as Capitol's LL400 Liquid Latex) • Do not use over existing cutback

Instructions For Use:

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the correct trowel making sure to maintain trowel notchings throughout the installation.
6. Allow the adhesive to flash for 15 minutes prior to installing the flooring material.
7. Apply only as much adhesive that can be installed within 45 minutes.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturers recommendations.
10. Clean wet adhesive and tools with white cloth and soap and water.

Caution:

Avoid contact with skin and eyes. If splashed in eyes, flush with copious amounts of water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed do not induce vomiting, call physician immediately. Keep container closed. KEEP OUT OF REACH OF CHILDREN

Trowel Requirements	
 <p>1/8 x 1/8 x 1/16 "V"</p> <p>13-14 square yards /gallon</p> <ul style="list-style-type: none"> • ActionBac® / Jute • Urethane (attached cushion) • Hot Melt 	 <p>1/8 x 1/8 x 1/8</p> <p>8-9 square yards /gallon</p> <ul style="list-style-type: none"> • Latex Unitary • Urethane Unitary • Woven
 <p>1/16 x 1/16 x 1/16</p> <p>18-19 square yards /gallon</p> <ul style="list-style-type: none"> • Pad to Floor (Double Glue) 	 <p>1/8 x 1/8 x 1/16</p> <p>6-7 square yards / gallon</p> <ul style="list-style-type: none"> • Double Glue Installations (Carpet to Pad)



Capitol USA, LLC
 300 Cross Plains Blvd. • PO Box 2023
 Dalton, GA 30722
 800-831-8381 • Fax: 706-277-5753
 Jim Walker ProSeries TechLine 888-234-8400
 Website www.capitolusa.com

Fast 095

Premium Performance Carpet Adhesive

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: Capitol USA, LLC
Address: 300 Cross Plains Blvd.
Dalton, GA 30720
Telephone #: 1-800-831-8381
Emergency Phone: 800-535-5053
Generic ID: Synthetic Rubber/ Resin Dispersion
DOT Hazard Classification: None
Product Identity: Fast 095 Premium Performance Carpet Adhesive

SECTION II - HAZARDOUS COMPONENTS

Mineral Spirits: % (weight) 2.1; PEL 100 ppm; TLV 100 ppm (CAS# 8052-41-3). Methanol: % (weight) 1.8; PEL 200 ppm; TLV 200 ppm (CAS# 67-56-1). SARA TITLE III Reportable: Methanol

SECTION III - PHYSICAL DATA

Initial Boiling Point: 212°F. Vapor Pressure: Same as water. Vapor Density (Air = 1.0): Same as water. Specific Gravity: 1.20. Percent Volatiles: 31-33%. G/L VOC (Calculated): 46.3

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point: NA. Explosive Limit (Product): NA. Extinguishing Media: NA. HAZARDOUS DECOMPOSITION PRODUCTS: None. SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus. UNUSUAL FIRE & EXPLOSION HAZARDS: None

SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level: NA. Threshold Limit Value: NA. EFFECTS OF EXPOSURE: Eyes - May cause slight transient (temporary) eye irritation. Skin - May cause slight irritation. Breathing - May cause slight irritation to upper respiratory tract. Swallowing- Not a likely route of entry under proper handling conditions. May cause vomiting. Symptoms may be the same as inhalation. FIRST AID: Skin - Soap and water. Eyes - Flush with water, lifting upper and lower lids occasionally. Ingestion- Do not induce vomiting. Call physician or transport to an emergency facility. Inhalation - If affected, remove individual to fresh air. Use only in well ventilated areas.

SECTION VI - REACTIVITY DATA

Stability: Stable. Incompatibility: Oxidizing materials. Hazardous Decomposition: Oxides of carbon, water and organic compounds of unknown structure. Hazardous Polymerization: Cannot Occur. Conditions To Avoid: None Known.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep out of sewer systems to prevent blockage due to polymer deposits. Soak up material with absorbent material (sand, sawdust, vermiculite) and place into closed container for disposal. Note: Dispose of all wastes in accordance with Federal, State and Local regulations.

SECTION VIII - PROTECTIVE EQUIPMENT

VENTILATION: Adequate ventilation is essential to prevent vapor build-up. Open all available windows and entrances to insure good ventilation. RESPIRATOR PROTECTION: Adequate ventilation is normally sufficient. If eyes begin to water or dizziness or headaches are experienced, increase fresh air supply, wear an NIOSH approved respirator, or leave the area. PROTECTIVE GLOVES: Wear protective gloves to prevent skin contact. EYE PROTECTION: Wear glasses or protective goggles to avoid splashes. OTHER PROTECTIVE EQUIPMENT: None required. WASH HANDS THOROUGHLY WITH SOAP AND WATER.

SECTION IX - SPECIAL PRECAUTIONS

Protect from freezing. Protect against physical damage. Store in cool, dry place (50°F - 90°F). Keep away from excessive heat. Use only in applications as stated on the label. Do not take internally. Close container after each use. Avoid skin and eye contact.

Ventilation with fresh air, including open doors and windows should be observed during any flooring installation. Operate HVAC systems at 100% fresh air intake before, during and after installation to eliminate lingering odors or particulate matter. KEEP OUT OF REACH OF CHILDREN

Capitol USA believes the data set forth herein is accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com